



CP-D6116GT-E8



XVR 5-IN-ONE

4 CH / 8 CH / 16 CH / CVI TVI AHD CVBS IPC / 720P 960P 1080P / HDD UP TO 6 TB

Key Features

XVR 5IN1 4 / 8 / 16 CH

- H.264 video compression
- Support HD-TVI, IPC,AHD and analog cameras with adaptive access
- Support Smart Face Detections&Premieter analysis
- Long transmission distance over coax cable
- Up to 4/8/16-ch synchronous playback

Model NO.	CP-D6104GT-E4	CP-D6108GT-E4	CP-D6116GT-F8
	4 CH	8 CH	16 CH
CPU/AD	HI3520D(V200)+2816	HI3520D(V300)+2816	HI3521A+2816
Video input	CVBS, TVI, AHD, CVI , IP Cameras		
Video&Audio output	1920×1080,1280×1024,1366×768,1280×720,1024×768		
Intelligent Analysis	1CH Face detection or 4CH Perimeter detection		
HDD Interface SATA	1 SATA interface	1 SATA interface	2 SATA interfaces
Max Capacity	Unlimited		
Network Interface	1 RJ45;10M/100M	1 RJ45;10M/100M	1 RJ45;10M/100M/1000M
USB Interface	2USB*2.0 Interfaces		3USB*2.0 Interfaces
Other Function	Bidirectional Talk two-way voice intercom function		
Motion Detection	Zones: 396(22×18)Multiple detection zones,Variable Sensitivity levels		
Regional Block	Each Channel support 4 Regional block pieces		
Picture Capture	Support JPEG Capture		
Video&Audio Decoding	Video Decoding Porfile H.264(Up to High Profile@Level4.2		
Synchronous Playback	Up to 4CH	Up to 4CH	Up to 8CH
Encoding Control	Qualified rate, variable bit rate is optional		
Video Bit Rate	32Kbps~4096Kbps		
Dimensions	250*235*45mm	250*235*45mm	335*275*50mm
Power DC	+12V 2A DC		+12V 4A